



Solution Review

COM2-24 APPLICATIONS PRESENTED BY POURIA NIKNAM

Index






- COM2-24 Features
- Energy Saving in HVAC Systems
- Receptacle Control Using COM2-24

COM2-24 Settings




IR Quattro COM2-24 / IR Quattro HD COM2-24



HVAC Stay-ON Time 1-120 min
HVAC Switch-ON Delay 30 sec – 10 min

COM2-24 Basic Wiring






Energy Efficiency and HVAC



Average energy cost saving of 38% by adding few controls to the HVAC system.



Energy Savings for OBC



US Department of Energy - Energy Savings for Occupancy Based Control (OBC) of Variable Air-Volume (VAV) Systems





Figure ES- 1. Savings from retrofit of OBC using common occupancy sensors for lighting and terminal boxes in the large office building that initially has no OBC for locations in the 15 U.S. climate zones. The numbered climate zones are color coded. [map adapted from DOE (2010)]

Private Office with HVAC Integration






Product	Qty.
IR CM COM2-24	1
TR 100	1
0-10V Slide Dimmer	1

Conference Room with HVAC Integration






Product	Qty.
DT Quattro COM2-24	2
TR 100	3
0-10V Slide Dimmer	2

Open Office Areas with HVAC Integration






Product	Qty.
IR Quattro HD DIM-24	4
IR Quattro HD COM2-24	4
TR 100	4
LV-3-W	1

Public Restrooms with Common Ex-Fan






Product	Qty.
US Quattro COM2-24	2
TR 100	3

ASHRAE 90.1 – Receptacle Control



As per section 8.4.2, 50% of receptacles in each area are to be controlled based on a time schedule or occupancy.



California Title 24 – Receptacle Control




As per section 135.1(d), 50% of receptacles are required to automatically turn off based on occupancy or after a vacancy of 20 minutes or less. Each uncontrolled receptacle must have at least one controlled receptacle within 6 feet.



Private Office with Receptacle Control






Product	Qty.
IR CM COM2-24	1
TR 100	2
0-10V Slide Dimmer	1

Conference Room with Receptacle Control





Product	Qty.
DT Quattro COM2-24	2
TR 100	3
0-10V Slide Dimmer	2



Thank You

Pouria Niknam
Sales Operations Manager
952-820-5128
pouria.niknam@steinel.net

Tech support 888-298-8298 tech@steinel.net